TOSHIBA

Satellite Pro® 6000 Series

Exceptional performance with integrated Wireless capability in a Mobile Desktop Replacement PC

Model(s):

Satellite Pro 6000:	<u>Part Numbers</u>
 PIII1000/14.1"TFT/256MB/30GB/DVD-CDRW/Mdm/LAN/WinXP Pro 	PS600U-01RCV9
 PIII1130/15.0"TFT/256MB/30GB/DVD-CDRW/Mdm/LAN/Wi-Fi/WinXP Pro 	PS600U-042D39
 PIII1200/15.0"TFT/256MB/40GB/DVD-CDRW/Mdm/LAN/Wi-Fi/WinXP Pro 	PS600U-04T739

Satellite Pro 6000 Small Business Series:

•	PIII1000/14.1"TFT/256MB/30GB/DVD-CDRW/Mdm/LAN/Win XP Pro/Office XP SB	PS600U-01RCV0W
•	PIII1000/14.1"TFT/256MB/30GB/DVD-CDRW/Mdm/LAN/Win XP Pro/Office XP Pro	PS600U-01RCV0X
•	PIII1130/15.0"TFT/256MB/30GB/DVD-CDRW/Mdm/LAN/Wi-Fi/WinXP Pro/Office XP SB	PS600U-042D30W
•	PIII1130/15.0"TFT/256MB/30GB/DVD-CDRW/Mdm/LAN/Wi-Fi/WinXP Pro/Office XP Pro	PS600U-042D30X
•	PIII1200/15.0"TFT/256MB/30GB/DVD-CDRW/Mdm/LAN/Wi-Fi/WinXP Pro/Office XP SB	PS600U-04T730W
•	PIII1200/15.0"TFT/256MB/30GB/DVD-CDRW/Mdm/LAN/Wi-Fi/WinXP Pro/Office XP Pro	PS600U-04T730X

Product Highlights

Performance

- Intel Mobile Pentium III 1000MHz (1.00GHz), 1130MHz (1.13GHz), or 1200MHz (1.20GHz) Processor-M
- 256MB of Main Memory (Expandable to 1024MB)

Slim Select Bay design

- 30.0GB or 40.0GB hard disk drive
- DVD-ROM/CDRW drive

Great Features

- 14.1" or 15.0" TFT active-matrix screen display
- 16MB Trident CyberALADDIN-T UMA internal video memory

Get On-Line

- Integrated V.90/56K modem
- Integrated 10/100 Ethernet LAN
- Optional or Integrated Wireless capabilities

System Characteristics

- Intel Mobile Pentium III 1000MHz (1.10GHz), 1130MHz (1.13GHz), or 1200MHz (1.20GHz) Processor-M w/SpeedStep Technology
- Integrated co-processor

L2 Cache

- 512KB Level 2 cache integrated on die
- 133MHz front side bus clock speed

Memory

- 256MB expandable to 1024MB
- Expansion memory: 256MB, SODIMM, PC133 SDRAM
- Data/Address Bus Width; 64-bit/32-bit
- BIOS ROM: CMOS Flash EPROM, 4MBit
- Trident CyberALADDIN-T (M1644) Chipset

Mass Storage

- Primary Hard Disk Drive: 30.0GB or 40.0GB hard disk drive, Enhanced IDE (ATA-5) interface, 9.5mm height, 0.2lbs, 13ms average access time (read/write), 3ms track to track seek time (read/write), 4200rpm drive rotation, supports PIO mode4, Ultra DMA mode5, & Multiword DMA mode2, Service Removable
- Slim Select Bay DVD-ROM/CDRW: Enhanced IDE (ATAPI)
 Interface; Hot Swappable (w/software); Compatibility: CD-ROM, CD-R (read/write), CD-RW (read/re-write), DVD-ROM, DVD-R (read only); 180ms (DVD-ROM)/130ms (CD-ROM) Access time (read/write); service removable
 - Software Decoder: InterVideo (WinDVD)

Graphics/Video

- 14.1" or 15.0" TFT active-matrix display; internal display supports up to 16M colors at 1024 x 768
- Trident CyberALADDIN-T graphics controller; 16MB UMA internal video memory
- 3D Graphics Accelerator, AGP bus support; 2D Graphics Accelerator, BitBLT hardware, Hardware cursor, Direct Draw support
- External Color Support:

640 x 480; 60/75/85Hz Non-Interlaced @16M 800 x 600: 60/75/85Hz Non-Interlaced @16M 1024 x 768; 60/75/85Hz Non-Interlaced @16M 1280 x 1024; 60/75Hz Non-Interlaced @16M 1600 x 1200; 60Hz Non-Interlaced @16M

Input Devices

 Keyboard: Full sized 85 keys with 12 function keys, 2.7mm key stroke, 6mm height; Dedicated Windows® & Application keys support; HotKey function; Integrated AccuPoint® II pointing device with Scroll button.

Expandability

 2 Expansion memory slot; 2 PC Card slots support 2 Type II or 1 Type III PC Cards; 32-bit CardBus ready

Communications

- Integrated V.90/56K modem; Data and fax support
- Integrated 10/100 Ethernet LAN
- Integrated Wireless LAN (PIII 1.13GHz and PIII 1.20GHz only)

Due to FCC limitations, speeds of 53kbps are the maximum permissible transmission rates during Download. Actual data transmission speeds will vary depending on line conditions.

Ports

- ECP parallel printer port
- Serial port
- RGB (monitor) port
- IR (Infrared) port
- 2 Universal Serial Bus port (USB)
- TV-Out NTSC/PAL output (RCA)
- PS/2 port- keyboard, mouse (Y-connector supported)
- RJ-45 LAN Port
- RJ-11 modem port
- Port Replicator expansion port
- Secure Digital (SD) card slot

Docking

Advanced Port Replicator

Physical Description

- Dimensions (LxWxH): 13.0" x 11.3" x 1.3"/1.4"
- Weight: 6.54 lbs (w/ 15.0" XGA, 256MB, 30GB, DVD, Modem, LAN, Wireless Antenna ready)

6.15 lbs (w/ 14.1" XGA, 256MB, 30GB, DVD,

Modem, LAN, Wireless Antenna ready)

 LED Indicators: Power, Power Save Mode, HDD, 2nd HDD, CD/DVD/DVD-CDRW, DC-IN, Caps Lock, Arrow, Numeric, Main Battery Charging Status, 2nd Battery Charging Status, System Sleep / Suspend status, SD Card, Wireless Communication

Sound

- ALI M1535 Sound Chip, AK4543 Codec Chip
- 16-bit stereo, full duplex support
- Built-in stereo speakers; Direct 3D Sound, DirectSound (supported by driver) and DirectMusic; MIDI Support
- Sound Volume (by Dial)
- Ports: External Microphone port, headphone port

Power Supply

AC Adapter: 75W external AC Adapter, 100-240V / 50-60Hz frequency (Universal) input voltage, 15V x 5A Output.
 Dimensions (LxWxH): 4.9" x 2.4" x 0.9"

Weight: 0.75lbs

Toshiba America Information Systems Inc. ("TAIS") shall not be liable for damages of any kind for use of this information, which is subject to change without notice. Copyright 2002 TAIS satellitepro_6000.doc Rev. 3 3/14/2003

Satellite Pro® 6000 Series (con.)

- Battery Pack: 6-cell, rechargeable, removable Lithium Ion (Lilon) battery, 10.8V x 3600mAh = 38.9Wh, (2nd battery = 10.8V x 3000mAh)
- Battery Saver (in Windows): Stand by, HDD Auto Off, Display Auto Off, Throttling, Hibernation
- Battery life (main batt/main + 2nd batt): 3+h/5+h
 Recharge time (main on/off, main + 2nd batt on/off): 2.5h
 Battery life may vary depending on product model, configuration, applications, power management settings and features utilized.
 Recharge time varies depending on usage. Battery may not charge while computer is consuming full power. After a period of time, the battery will lose its ability to perform at maximum capacity and will need to be replaced. This is normal for all batteries. To purchase a new battery pack, see the accessories information that shipped with your computer or visit www.accessories.toshiba.com

Security

 Slot for computer lock, PC Card (sliding lock), HDD and memory (by screw only), Built-in Modem/LAN (screw only), Selectable Bay Device, User Power-on password, Setup Security, CPU serial No. security, HDD Password, Keyboard Lock (by HotKey), Screen Blank (by Hotkey), Screen Saver (by software).

Bios

 TSETUP, APM, ACPI, PnP, VESA, DPMS, DDC, SM BIOS, PC BIOS support

Operating System

- Microsoft® Windows XP Pro pre-installed
- Microsoft® Windows 2000 pre-installed link on CBCD
- Microsoft® Windows 98 component drivers on the Web

Additional Software

- Microsoft® Office XP SB (Small Business) * (on some models-See Product/Part Numbers below)
- Microsoft® Office XP Professional * (on some models- See Product/Part Numbers below)
- Intuit Quicken Basic 2001
- Norton AntiVirus 2002
- AOL (3 –Month offer)
- Adobe Acrobat Reader
- Microsoft Internet Explorer
- Toshiba Custom Utilities
- Satellite Series Online Documentation
- <u>Toshiba Great Software Offer</u>: Receive your choice of two software titles. The software selection includes titles from the follow categories; productivity, education/reference, creativity and entertainment

Warranty

1 year parts, labor and battery

Environmental Specifications

- Temperature: Operating: 5° to 35°C (41° to 95°F); Non-operating: -20° to 65°C (-4° to 149°F)
- Thermal gradient: Operating: 15°C per hour maximum; Nonoperating: 20°C per hour maximum
- Relative Humidity: Operating: 20% to 80% non-condensing; Non-operating: 10% to 90% non-condensing
- Altitude (relative to sea level): Operating: -60 to 3000 meters;
 Non-operating: -60 to 10,000 meters
- Shock: Operating: 7G, 1.5G(when CD/DVD-ROM drive installed); Non-operating: 60G
- Vibration: Operating: 0.2G, 0.25G (when CD/DVD-ROM drive installed); Non-operating: 1.0G

Accessories

KINGSTON Memory

KTT-SO133/128 128MB SDRAM Memory KTT-SO133/256 256MB SDRAM Memory KTT-SO133/512 512MB SDRAM Memory

Cases (Targus)

NWCTM1 Metropolitan Carrying Case (koskin)
NWCSS1 Suburban Carrying Case (nylon)
NWCEB1 Expedition Backpack

NWCER1 Excursion Roller

TOSHIBA SD Memory

SD-M3203M-A 32MB SD-M6403M-A 64MB SD-M1283M-A 128MB

Other Accessories PA3083U-1ACA

PA3083U-1ACA
PA3128U-1BRS
PA3091U-1CHG
PA3109U-1FDD
PA3116U-1H30
Universal AC Adapter
Li-lon Battery
Battery Charger
Floppy Disk Drive (Black)
30GB Hard Disk Drive

PA3129U-1BRS Slim SelectBay Battery
PA3134U-1ETC Slim SelectBay Adapter (Black)
PA3135U-1CDD Slim SelectBay CD-ROM (Black)
PA3138U-1CD1 Slim SelectBay CD-R/RW (Black)
Slim SelectBay CD-R/RW (Black)

PA3137U-1CD2 Slim SelectBay CD-RW/DVD-ROM (Black)

PA3066U-1PCC FingerPrint Reader
PA3082U-1PRP Advanced Port Replicator
PA3070U-7MPC Mini PCI Card 128-bit encryption

Wi-Fi (Agere)

8484415560 Orinoco Wireless LAN PC Card (Gold)

8485582350 Orinoco AP-1000 Access Point w/128wep Gold Card 8485878380 Orinoco AP-500 Access Point

8485463880 Orinoco RG-1000 Residential Gateway 8485893390 Orinoco Range Extending Antenna

Product/Part Numbers/UPC

Satellite Pro 6000 (PIII 1.00GHz)	PS600U-01RCV9
Satellite Pro 6000 (PIII 1.13GHz)	PS600U-042D39
Satellite Pro 6000 (PIII 1.20GHz)	PS600U-04T739
* Satellite Pro 6000 (PIII 1.00GHz) (Office XP SB)	PS600U-01RCV0W
* Satellite Pro 6000 (PIII 1.00GHz) (Office XP Pro)	PS600U-01RCV0X
* Satellite Pro 6000 (PIII 1.13GHz) (Office XP SB)	PS600U-042D30W
* Satellite Pro 6000 (PIII 1.13GHz) (Office XP Pro)	PS600U-042D30X
* Satellite Pro 6000 (PIII 1.20GHz) (Office XP SB)	PS600U-04T730W
* Satellite Pro 6000 (PIII 1.20GHz) (Office XP Pro)	PS600U-04T730X

Toshiba America Information Systems Inc. ("TAIS") shall not be liable for damages of any kind for use of this information, which is subject to change without notice. Copyright 2002 TAIS satellitepro_6000.doc Rev. 3 3/14/2003